

Specifications for some of our range of tungsten heads.

### Arri Fresnels



	300W	650W	1KW	2KW
Type	Arri	Arri	Arri	Arri
Lens Size	80mm	112mm	130mm	175mm
Weight	1.5Kg	2.7Kg	4.5Kg	6Kg
Spot Angle	14°	16°	15°	13°
Flood Angle	62°	60°	60°	60°
Spot Lux	2320@3m	2610@3m	2800@5m	6100@5m
Flood Lux	400@3m	1190@3m	680@5m	1070@5m

### LTM Fresnels



	150W	300W
Type	Pepper	Pepper
Lens Size	50mm	80mm
Weight	1Kg	1.5Kg
Spot Angle	14°	14°
Flood Angle	42°	62°
Spot Lux	3500@1m	2320@3m
Flood Lux	1500@1m	400@3m

### Quartzcolor Fresnels



	2KW	1.25/1.25KW	2KW	2.5/2.5KW	5KW	10KW
Type	Bambino	Castor	Castor	Pollux	Bambino	Vega
Lens Size	150mm	300mm	300mm		250mm	350mm
Weight	5.7Kg	12.5Kg	12.5Kg	16.5Kg	9Kg	24Kg
Spot Angle	18°	8.5°	8.5°	12.5°	23°	18°
Flood Angle	66°	45°	45°	56.5°	65°	59°
Spot Lux	1550@10m	4075@5m	4075@5m	5000@10m	5500@10m	
Flood Lux	190@10m	525@5m	525@5m	750@10m	1300@10m	1700@10m

### Source 4 Profiles



	5°	10°	19°	26°	36°	50°
Weight	8.6Kg	6.8Kg	6.8Kg	6.8Kg	6.8Kg	6.8Kg
Lux	1334@32m	1250@26m	1022@17m	688@15m	720@10m	602@7.6m

### Source 4 Zoom Profiles

	15° - 30°	25° - 50°
Weight	8.6Kg	8.6Kg
Spot Lux	1258@16.5m	1354@10m
Flood Lux	968@10m	522@10m

### PAR Lamps



Type	Floor lamp	Single	Bar of 4	Bar of 4 ACL	Bar of 6
Weight	2.5Kg	3Kg	15Kg	15Kg	25Kg
Connector	16A	16A	Socapex	16A	Socapex

### Lamp Types

Type	Voltage	Intensity	Width	Height
CP60	240V	320,000cd	12°	9°
CP61	240V	270,000cd	14°	10°
CP62	240V	125,000cd	24°	11°
CP63	240V		57°	21°

All lamps shown above are 1000W 3600°K.

