



Dimming Systems


AVOLITES DMX DIMMER RACK 48 x 5K or 24 x 10K

Weight: 220Kg
 Dimensions: 950mm x 570mm x 1170mm
 Control Input: DMX-512 via 2 x 5 pin XLR (A/B switchable)
 Power Input: 5 x 400A Powerlok connectors with current and voltage metering
 RCD: Adjustable keyswitchable RCD
 Aux Output: 1 x 32A 3Ø CEE-17 socket, 1 x 16A CEE-17 socket
 Load Patch: Fully patchable via 3 pin Wieland patch cables (2.5KW only)
 Patch Legs: 4 legs per rack, each leg may be one of:
 12 x 2.5KW Parallel on 19 pin Socapex
 12 x 5KW on 32A CEE-17 sockets
 6 x 10KW on 63A CEE-17 sockets



AVOLITES DMX DIMMER RACK 72 x 2.5K

Weight: 256Kg
 Dimensions: 950mm x 570mm x 1430mm
 Control Input: DMX-512 via 2 x 5 pin XLR (A/B switchable)
 Power Input: 5 x 400A PowerLok connectors
 RCD: 6 x fully adjustable RCDs
 Output: 19 pin Socapex
 Aux Output: 1 x 16A CEE-17 socket
 Load Patch: Fully patchable via 3 pin Wieland patch cables



PARADIM DMX PATCHABLE DIMMER PACK 6 x 2.5K

Weight: 35kg
 Dimensions: 805mm x 540mm x 270mm
 Control Input: DMX-512 via 5 pin XLR
 Power Input: 63A 1Ø
 RCD: Requires RCD Supply
 Output: 2 x 19 pin Socapex Connectors



AVOLITES DMX DIMMER PACK 12 x 2.5K

Weight: 80Kg
 Dimensions: 805mm x 540mm x 270mm
 Control Input: DMX-512 via 5 pin XLR
 Power Input: 125A 1Ø
 RCD: Requires RCD supply
 Output: 12 x 16A 1Ø / 6 x 32A 1Ø
 Built-in control desk



ETC DMX DIMMER PACKS 12 x 2.5K

Weight: 75kg
 Dimensions: 580mm x 350mm x 250mm
 Local Control: Built-in control Knobs
 Control Input: DMX-512 via 5 pin XLR
 Power Input: 63A 3Ø
 RCD: Requires RCD Supply
 Output: 12 x 16A 1Ø



DMX DIMMER PACKS 5 x 5K or 2 x 10K

Weight: 25kg
 Dimensions: 620mm x 465mm x 185mm
 Local Control: Built-in control Knobs
 Control Input: DMX-512 via 5 pin XLR
 Power Input: 125A 1Ø
 RCD: Fitted with RCD Protection
 Output: 5 x 32A 1Ø / 2 x 63A 1Ø



SINGLE CHANNEL DIMMERS

Each dimmer has a built-in control fader

Capacity:	10KW	5KW	2.5KW
Weight:	3.9Kg	1.4Kg	1.1Kg
Dimensions:	420x130x155		

