



Fluorescent Lights

KINO FLO IMAGE 80

Softlight for ChromaKey cyc lighting and blue screen developed especially for the Digital Video capture market

Light o/p	642 lux @ 3m
Weight	16.7kg
Dimensions	1384mm x 829mm x 159mm
Control	DMX
Current	5A @ 230V
Tubes	10



KINO FLO DIVA 400

Lightweight location lighting developed especially for the Digital Video capture market switchable between 4 tubes or 2 tubes

Light o/p	334 lux @ 3m
Weight	6.5kg
Dimensions	660mm x 305mm x 159mm (w/ 140mm barn doors)
Current	1.1A @ 230V
Tubes	4



KINO FLO WALL-O-LITE

Specially designed softlight with individual DMX control of each tube. Can be used side-by-side to create a large seamless wall of light

Light o/p	810 lux @ 3m
Weight	22.3kg
Dimensions	1238mm x 673mm x 146mm
Control	DMX
Current	5A @ 230V
Tubes	10



KINO FLO KITS

Lightweight compact fluorescent fixtures with 2' or 4' tubes. All units have an output frequency of 25KHz. Available in daylight 5500°K, Tungsten 3200°K and Super Tungsten 2900°K

	1 x 2'	2 x 2'	4 x 2'	1 x 4'	2 x 4'	4 x 4'
Light o/p (lux @ 3m)	43	97	194	108	216	378
Weight (Kg)	0.91	1.81	2.95	1.81	3.18	4.76
Length (mm)	679	679	679	1308	1308	1308
Current	0.5A	0.9A	1.8A	0.7A	1.3A	2.5A



PHOTON BEARD

DMX controlled softlight, available with daylight or tungsten tubes

Type	Highlight 110	Highlight 220
Light o/p	240 lux @ 3m	360 lux @ 3m
Weight	3.5kg	5kg
Dimensions (mm)	637 x 150 x 125	637 x 260 x 135
Control	DMX	DMX
Power	110W	220W
Tubes	2 x 55W	4 x 55W



MINI-FLO KIT

Miniature 12V fluorescent light.

Power Supply:	12V via battery or adapter
Weight:	227g
Size:	260mm x 70mm x 64mm
Output Freq.:	50KHz
Light Output:	110 Lux @ 1m



MICRO-FLO KIT

Sub miniature 12 volt fluorescent light

Power Supply:	12V DC or 240V AC
Weight:	54g
Size:	84mm x 25mm x 22mm
Output Freq.:	25KHz
Light Output:	184 Lux @ 200mm

